


Fixture Lengths

CSS-R | RAS


Fixture Type

Approval

Continuous Run Individual Cable/Arm Centers



Stand Alone Cable/Arm Centers & Overall Length



Fixture Length	Cable/Arm Centers (in)	Fixture Length	Cable/Arm Centers (in)	Fixture Length	Cable/Arm Centers (in)
2'	26.000"	2'	26.000"	2'	26.000"
3'	38.000"	3'	38.000"	3'	38.000"
4'	50.000"	4'	50.000"	4'	50.000"


Fixture Length	Cable/Arm Centers (in)	Overall Length (in)
2'	26.000"	27.125"
3'	38.000"	39.125"
4'	50.000"	51.125"

Continuous Run Lengths and Fixture Length Segments

Nominal Length (ft)	CSS-R/RAS Overall Length (in)	Fixture Length Segments
6	6' - 5.125"	3-3
7	7' - 5.125"	4-3
8	8' - 5.125"	4-4
9	9' - 7.125"	3-3-3
10	10' - 7.125"	4-4-2
11	11' - 7.125"	4-4-3
12	12' - 7.125"	4-4-4
13	N/A	N/A
14	13' - 9.125"	4-3-3-3
15	14' - 9.125"	4-4-3-3
16	15' - 9.125"	4-4-4-3
17	16' - 9.125"	4-4-4-4
18	17' - 11.125"	4-4-4-3-2
19	18' - 11.125"	4-4-4-4-2
20	19' - 11.125"	4-4-4-4-3

Nominal Length (ft)	CSS-R/RAS Overall Length (in)	Fixture Length Segments
21	20' - 11.125"	4-4-4-4-4
22	22' - 1.125"	4-4-4-4-3-2
23	23' - 1.125"	4-4-4-4-4-2
24	24' - 1.125"	4-4-4-4-4-3
25	25' - 1.125"	4-4-4-4-4-4
26	26' - 3.125"	4-4-4-4-4-3-2
27	27' - 3.125"	4-4-4-4-4-4-2
28	28' - 3.125"	4-4-4-4-4-4-3
29	29' - 3.125"	4-4-4-4-4-4-4
30	30' - 5.125"	4-4-4-4-4-4-3-2
31	31' - 5.125"	4-4-4-4-4-4-4-2
32	32' - 5.125"	4-4-4-4-4-4-4-3
33	33' - 5.125"	4-4-4-4-4-4-4-4
34	33' - 7.125"	4-4-4-4-4-4-4-2-2
35	34' - 7.125"	4-4-4-4-4-4-4-3-2

Nominal Length (ft)	CSS-R/RAS Overall Length (in)	Fixture Length Segments
36	35' - 7.125"	4-4-4-4-4-4-4-4-2
37	36' - 7.125"	4-4-4-4-4-4-4-4-3
38	37' - 7.125"	4-4-4-4-4-4-4-4-4
39	38' - 9.125"	4-4-4-4-4-4-4-4-3-2
40	39' - 9.125"	4-4-4-4-4-4-4-4-4-2
41	40' - 9.125"	4-4-4-4-4-4-4-4-4-3
42	41' - 9.125"	4-4-4-4-4-4-4-4-4-4
43	42' - 11.125"	4-4-4-4-4-4-4-4-4-3-2
44	43' - 11.125"	4-4-4-4-4-4-4-4-4-4-2
45	44' - 11.125"	4-4-4-4-4-4-4-4-4-4-3
46	45' - 11.125"	4-4-4-4-4-4-4-4-4-4-4
47	47' - 1.125"	4-4-4-4-4-4-4-4-4-4-3-2
48	48' - 1.125"	4-4-4-4-4-4-4-4-4-4-4-2
49	49' - 1.125"	4-4-4-4-4-4-4-4-4-4-4-3
50	50' - 1.125"	4-4-4-4-4-4-4-4-4-4-4-4



#825-00149
V-0117